



2014B LATHE

PM1-482, PM1-483

Engineered for Superior Turning Performance.

The Powermatic 2014B Lathe is engineered for woodturners who demand professional-level performance in a compact, versatile machine. Built with the strength, control, and precision serious woodworkers demand, it is engineered to reduce vibration, expand capacity, and deliver consistent performance. From its heavy cast iron construction to smooth variable-speed operation, every detail is designed for a better turning experience. The result is greater control, smoother cuts, and a difference you can feel in every pass.

POWERMATIC®

THE GOLD STANDARD

Learn more at powermatic.com

2014B LATHE

PM1-482, PM1-483

Durability

A heavy-duty cast iron construction across the bed, legs, headstock and tailstock give the 2014B the rigidity serious turners demand. An improved stand adds stability for smoother, more confident work.

Versatility

Built to adapt, the 2014B gives you more ways to work with confidence. A sliding headstock and tailstock, optional bed extension, adjustable height, and 24-position indexing expand your turning range while preserving control and repeatability.

Performance

A 1 HP VFD motor and variable speeds from 15 to 3,600 RPM give the 2014B smooth, precise control through every pass. With 20" between centers and a 14" swing, it is built to handle a wide range of turning applications with confidence.

Confidence

Backed by Powermatic's Gold Glove Service and an industry-leading 5-year warranty, the Powermatic 2014B Lathe is built to earn trust long after it is in the shop.



MODEL NO.	2014B LATHE WITH STAND	2014B BENCHTOP LATHE
Stock Number	PM1-482	PM1-483
Warranty	5 Years	5 Years
Motor Power	1 HP	1 HP
Motor Speed	1,720 RPMs	1,720 RPMs
Phase	1 PH	1 PH
Motor Output Voltage	230V	230V
Recommend Circuit Size (Amps.)*	15	15
Construction	Cast Iron (Bed, lathe, legs)	Cast Iron (Bed, lathe, legs)
Distance Between Centers	20"	20"
Swing Over	14-1/4"	14-1/4"
Input Power	115V	115V
# of Indexing Positions	24	24
Quill Diameter, Taper & Travel	3/8", #2 Morse, 4-1/4"	3/8", #2 Morse, 4-1/4"
Full Assembly Overall Dimension (L x W x H)	52" x 25" x 48-1/2"	52" x 24" x 18"
Net Weight (lbs.)	266 lbs.	187 lbs.
Shipping Weight (lbs.)	299 lbs.	212 lbs.
Tool Rest Construction and Size	Hardened Steel Top Rod, Cast Iron Base, 8" Tool Rest	Hardened Steel Top Rod, Cast Iron Base, 8" Tool Rest

AVAILABLE ACCESSORIES	STOCK NO.
2014B Lathe Stand	PM1-484
2014B Lathe 13" Bed Extension	PM1-485
2014B Lathe LED Lamp	PM9-6294924

* When using long extension cords, circuit size requirements may differ. Most VFD lathes are not compatible with standard GFCI outlets. Consult a certified electrician and/or local electric codes for detailed requirements.



Improved Magnetic Backed Repositionable Control Box
For more convenience and safety.



New Tool Rest With Hardened Steel Top Rod
For long lasting durability.



New Adjustable Leg Stand Design
Provide superior vibration dampening and stability.



1 HP VFD Industrial Motor With 3PH Output
Delivers smooth variable-speed performance and power.



Sliding Headstock
Provide versatility for outboard turning for large projects.

POWERMATIC

THE GOLD STANDARD

Learn more at powermatic.com